

CNC 12000 HYDRAULIC WINCH



MOBILE AND INDUSTRIAL HYDRAULIC

- * MAXIMUM PULL FORCE: 12.000 kg
- * MAXIMUM ROPE LENGTH: 60 mt
- * MAXIMUM ROPE DIAMETER: 16 mm
- * HYDROMOTOR: WR-160 cc
- * MAXIMUM OPERATING PRESSURE: 170 bar
- * MAXIMUM PUMP FLOW: 60 lt/min
- * CONVERSION RATIO: 36/1
- * RECOMMENDED OIL: 80 W / 1.5 lt
- * PRODUCT WEIGHT: 200 kg
- * LONG-LIFE HYDRAULIC BRAKE SYSTEM POWERED BY MULTIPLE DISCS.
- * THROUGH HEAT TREATMENT EXTRA REINFORCE PLANETARY GEAR SYSTEM MADE OF SPECIAL STEEL
- * HIGH STRENGTH CASTING BODY AND CAST ROLLER.
- * HIGH TORQUE HYDROMOTOR.



NUMBER OF ROPE WRAPS	PULL CAPACITY	ROPE PULLING CAPACITY	ROPE LENGTH
1. WRAP	12,000 KG	MIN/5MT	8,5 MT
2. WRAP	10,560 KG	MIN/6MT	18 MT
3. WRAP	9,300 KG	MIN/8,5MT	31 MT
4. WRAP	8,200 KG	MIN/8,5MT	45 MT
5. WRAP	7,200 KG	MIN/9,5MT	60 MT

ATTENTION!

- * ALWAYS LEAVE THE FIRST FIVE WRAPS ON.
- * DO NOT FORGET TO OPEN THE A-B TANK LINE FROM THE ROPE DRUM CONTROL VALVE.
- * DO NOT FORGET TO OPEN HYDROMOTOR LEAK LINE.

