

CNC 3200 HYDRAULIC WINCH



MOBILE AND INDUSTRIAL HYDRAULIC

- * MAXIMUM PULL FORCE: 3.200 kg
- * MAXIMUM ROPE LENGTH: 53 mt
- * MAXIMUM ROPE DIAMETER: 12 mm
- * HYDROMOTOR: WP-160 cc
- * MAXIMUM OPERATING PRESSURE: 175 bar
- * MAXIMUM PUMP FLOW: 60 lt/min
- * CONVERSION RATIO: 6,2/1
- * RECOMMENDED OIL: 80 W / 0.7 lt
- * PRODUCT WEIGHT: 80 kg
- * LONG-LIFE HYDRAULIC BRAKE SYSTEM POWERED BY MULTIPLE DISCS.
- * THROUGH HEAT TREATMENT EXTRA RAINFORCE PLANETARY GEAR SYSTEM MADE OF SPECIAL STEEL
- * HIGH STRENGTH CASTING BODY AND CAST ROLLER.
- * HIGH TORQUE HYDROMOTOR.



NUMBER OF ROPE WRAPS	PULL CAPACITY	ROPE PULLING CAPACITY	ROPE LENGTH
1. WRAP	3,200 KG	MIN/18MT	5,5 MT
2. WRAP	2,880 KG	MIN/23MT	12 MT
3. WRAP	2,600 KG	MIN/27MT	20 MT
4. WRAP	2,230 KG	MIN/32MT	30 MT
5. WRAP	2,100 KG	MIN/36MT	40 MT
6. WRAP	1,890 KG	MIN/40MT	53 MT

ATTENTION!

- * ALWAYS LEAVE THE FIRST FIVE WRAPS ON.
- * DO NOT FORGET TO OPEN THE A-B TANK LINE FROM THE ROPE DRUM CONTROL VALVE.
- * DO NOT FORGET TO OPEN HYDROMOTOR LEAK LINE.

