

CNC 6200 HYDRAULIC WINCH



MOBILE AND INDUSTRIAL HYDRAULIC

- * MAXIMUM PULL FORCE: 6.200 kg
- * MAXIMUM ROPE LENGTH: 53 mt
- * MAXIMUM ROPE DIAMETER: 12 mm
- * HYDROMOTOR: WP-315 cc
- * MAXIMUM OPERATING PRESSURE: 140 bar
- * MAXIMUM PUMP FLOW: 60 lt/min
- * CONVERSION RATIO: 6,2/1
- * RECOMMENDED OIL: 80 W / 0.7 lt
- * PRODUCT WEIGHT: 80 kg
- * LONG-LIFE HYDRAULIC BRAKE SYSTEM POWERED BY MULTIPLE DISCS.
- * THROUGH HEAT TREATMENT EXTRA RAINFORCE PLANETARY GEAR SYSTEM MADE OF SPECIAL STEEL
- * HIGH STRENGTH CASTING BODY AND CAST ROLLER.
- * HIGH TORQUE HYDROMOTOR.



NUMBER OF ROPE WRAPS	PULL CAPACITY	ROPE PULLING CAPACITY	ROPE LENGTH
1. WRAP	6,200 KG	MIN/9MT	5,5 MT
2. WRAP	5,550 KG	MIN/11,4MT	12 MT
3. WRAP	5,000 KG	MIN/13,7MT	20 MT
4. WRAP	4,500 KG	MIN/16MT	30 MT
5. WRAP	4,150 KG	MIN/18MT	40 MT
6. WRAP	3,700 KG	MIN/20MT	53 MT

ATTENTION!

- *ALWAYS LEAVE THE FIRST FIVE WRAPS ON.
- *DO NOT FORGET TO OPEN THE A-B TANK LINE FROM THE ROPE DRUM CONTROL VALVE.
- *DO NOT FORGET TO OPEN HYDROMOTOR LEAK LINE.

