



### DUNLOPHIFLEX

DIMENSION	1 SN/1 AT (SINGLE WIRE)	2 SN/2 AT (DOULE WIRE)	POWERFLEX BiO 5000 PSI (4SP) (FOUR WIRE)	PRESSURE	POWERFLEX BiO 6000 PSI (4SH) (FOUR WIRE)	PRESSURE
	PRICE (Euro)	PRICE (Euro)	PRICE (Euro)	(bar)	PRICE (Euro)	(bar)
3/16"				-		-
1/4"				450		-
5/16"				-		-
3/8"				445		-
1/2"				420		-
5/8"				350		-
3/4"				420		-
1"				380		-
1 1/4"				350		420
1 1/2"				290		420
2"				-		-



### ALFAGOMMA

DIMENSION	1 SN/R1 AT (SINGLE WIRE)	2 SN/R2 AT (DOUBLE WIRE)	4SP (FOUR WIRE)	PRESSURE	4SH (FOUR WIRE)	PRESSURE
	PRICE (Euro)	PRICE (Euro)	PRICE (Euro)	(bar)	PRICE (Euro)	(bar)
1/4"				-		-
5/16"				-		-
3/8"				445		-
1/2"				415		-
5/8"				350		-
3/4"				380		420
1"				320		380
1 1/4"				-		350
1 1/2"				-		290
2"				-		250



### ALFAGOMMA

DIMENSION	SAE 100 R15 (SIX WIRE)	R13	R4	R6	FP2 DOUBLE HOSE	1SC	2SC
	PRESSURE (bar)	PRESSURE(bar)	PRESSURE(bar)	PRESSURE(bar)	PRESSURE(bar)	PRESSURE(bar)	PRESSURE (bar)
1/4"	-	-	-	28	-	-	-
5/16"	-	-	-	28	-	-	-
3/8"	-	-	-	28	330	300	350
1/2"	-	-	-	28	275	230	310
5/8"	-	-	-	24	-	189	280
3/4"	-	-	300	-	-	153	240
1"	-	380	250	-	-	-	-
1 1/4"	420	350	200	-	-	-	-
1 1/2"	420	350	150	-	-	-	-
2"	420	350	100	-	-	-	-
2" 1/2	-	-	60	-	-	-	-
3"	-	-	60	-	-	-	-
4"	-	-	45	-	-	-	-

## FORCESTREAM R1 AT/1SN

SAE 100 R1 AT/DIN-EN 853 1SN

TS EN 853

Made of special synthetic rubber resistant to hydraulic oils. Hydraulic circuits requiring high pressure in construction and agricultural machinery.



DIMENSION	OD (mm)	WP (Bar)	PP (Bar)	KYÇ/r (mm)	WEIGHT (gr/m)
3/16"	11,6	250	1100	90	180
1/4"	13,2	225	1030	100	220
5/16"	14,8	215	970	115	260
3/8"	17,2	180	820	130	330
1/2"	20,4	160	700	180	410
5/8"	23,5	130	600	200	470
3/4"	27,5	105	500	240	585
1"	35,4	88	375	300	870
1 1/4"	43,5	63	280	420	1205
1 1/2"	50	50	260	500	1400
2"	63,6	40	250	630	1910
2" 1/2"	76,5	40	200	762	2535
3"	88,5	35	160	900	2710

## FORCESTREAM R2 AT/2SN

SAE 100 R2 AT/DIN-EN 853 2SN

TS EN 853

Made of special synthetic rubber resistant to hydraulic oils. Hydraulic circuits requiring high pressure in construction and agricultural machinery.




DIMENSION	OD (mm)	WP (Bar)	PP (Bar)	KYÇ/r (mm)	WEIGHT (gr/m)
3/16	13,3	415	1850	90	295
1/4	15	400	1700	100	375
5/16	16,5	350	1550	115	430
3/8	18,9	330	1450	130	540
1/2	22,2	275	1300	180	640
5/8	25,2	250	1050	200	750
3/4	29,2	215	920	240	925
1"	37,2	165	690	300	1.290
1" 1/4	47,3	125	620	420	1890
1" 1/2	53,7	90	520	500	2100
2"	66,7	78	420	630	2760
2" 1/2	79,8	69	300	760	3810
3"	91,9	50	240	900	4040

## POWERSTREAM 4SP

TS EN 856 4SP

Spiral Steel Wire Hydraulic

Resistant to mineral, vegetable and glucose-based hydraulic oils. In systems that will be exposed to very high peak pressures and difficult conditions.




DIMENSION	OD (mm)	WP (Bar)	PP (Bar)	KYÇ/r (mm)	WEIGHT (gr/m)
1/4"	17,6	450	1800	150	565
3/8"	21	445	1780	180	730
1/2"	24,4	415	1660	230	865
5/8"	28,0	350	1400	250	1035
3/4"	32,0	350	1400	300	1485
1"	39,1	280	1120	340	1900

## POWERSTREAM 4SH

TS EN 856 4SH

Spiral Steel Wire Hydraulic

Resistant to mineral, vegetable and glucose-based hydraulic oils. In systems that will be exposed to very high peak pressures and difficult conditions.




DIMENSION	OD (mm)	WP (Bar)	PP (Bar)	KYÇ/r (mm)	WEIGHT (gr/m)
3/4"	32,0	420	1680	280	1465
1"	38	380	1520	340	2035
1 1/4"	45,2	350	1400	460	2385
1 1/2"	53,0	290	1160	560	3185
2"	67,6	250	1000	700	4365

## TWINSTREAM 2 SC - İkiZ

DIN-EN 857 2SC

TS EN 857 Flat Top

Made of special synthetic rubber resistant to hydraulic oils. Hydraulic circuits requiring high pressure in construction and agricultural machinery.



DIMENSION	OD (mm)	WP (Bar)	PP (Bar)	KYÇ/r (mm)	WEIGHT (gr/m)
1/4"x1/4"	13.5x13.5	400	1850	45	600
5/16"x5/16"	15.5x15.3	350	1700	55	690
3/8"x3/8"	17.4x17.4	330	1550	65	855
1/2"x1/2"	21x21	275	1270	80	1185

## SELTEX R6

EN 854 R6 SAE 100 R6

TS EN 854 R6

Made of special synthetic rubber resistant to high-temperature hydraulic oils. High pressure hydraulic oil, fuel oil and grease oil discharge.



DIMENSION	OD (mm)	WP (Bar)	PP (Bar)	KYÇ/r (mm)	WEIGHT (gr/m)
3/16	10,7	34	250	35	90
1/4	12,3	28	200	45	105
5/16	13,9	28	200	65	125
3/8	15,5	28	200	75	150
1/2	19,5	28	200	90	225
5/8	22,6	24	140	115	260
3/4	25,8	21	130	140	315
1"	33,2	20	100	150	470



DIMENSION	1 SN/1 AT (SINGLE WIRE)	2 SN/2 AT (DOUBLE WIRE)	4SP (FOUR WIRE)	PRESSURE	4SH (FOUR WIRE)	PRESSURE
	PRICE (Euro)	PRICE (Euro)	PRICE (Euro)	(bar)	PRICE (Euro)	(bar)
3/16"				-		-
1/4"				450		550
5/16"				445		540
3/8"				445		520
1/2"				415		280
5/8"				350		450
3/4"				350		420
1"				280		380
1 1/4"				210		325
1 1/2"				185		290
2"				165		250

**FIREFLEX R1**



DIMENSION	OD (mm)	WP (Bar)	PP (Bar)	KYC/r (mm)	WEIGHT (gr/m)
3/16"	11,6	250	1100	90	180
1/4"	13,2	225	1030	100	220
5/16"	14,8	215	970	115	260
3/8"	17,2	180	820	130	330
1/2"	20,4	160	700	180	410
5/8"	23,5	130	600	200	470
3/4"	27,5	105	500	240	585
1"	35,4	88	375	300	870
1 1/4"	43,5	63	280	420	1205
1 1/2"	50	50	260	500	1400
2"	63,6	40	250	630	1910
2 1/2"	76,5	40	200	762	2535
3"	88,5	35	160	900	2710

**FIREFLEX R2**



DIMENSION	OD (mm)	WP (Bar)	PP (Bar)	KYC/r (mm)	WEIGHT (gr/m)
3/16"	13,3	415	1850	90	295
1/4"	15	400	1700	100	375
5/16"	16,5	350	1550	115	430
3/8"	18,9	330	1450	130	540
1/2"	22,2	275	1300	180	640
5/8"	25,2	250	1050	200	750
3/4"	29,2	215	920	240	925
1"	37,2	165	690	300	1.290
1 1/4"	47,3	125	620	420	1890
1 1/2"	53,7	90	520	500	2100
2"	66,7	78	420	630	2760
2 1/2"	79,8	69	300	760	3810
3"	91,9	50	240	900	4040

**POLYETHYLENE SPIRAL PROTECTIVE**

Protective cover for hoses and cables, optionally made of polyethylene or polyamide.



ID (mm)	OD (mm)	WEIGHT (gr/m)	IN THE BOX (meter)
7,50	10	32	400
9,50	12	39	300
13	16	64	150
16	20	106	100
20	25	166	60
24	29	196	50
27	32	217	40
30	35	239	30
35	40	276	25
44	50	415	15
50	60	810	10
60	70	958	8
65	75	1032	5
75	85	1180	5
80	90	1252	5
100	110	1548	2,5

**BOSPHORUS FOOD**

STEEL SPIRAL SUITABLE FOR FOOD



ID		PP bar	VACUUM m/H2O	WEIGHT gr/m
inch	mm			
1/2"	12	21	9	180
	14	18	9	200
5/8"	16	18	9	225
	18	18	9	280
3/4"	20	15	9	340
	25	15	9	510
1"	30	13	9	600
	32	13	9	650
1 1/4"	35	12	9	730
	38	12	9	800
1 1/2"	40	9	9	870
	45	9	8	1100
2"	51	9	8	1200
	60	7	7	1800
2 1/2"	63	7	7	1950
	70	6	7	2200
3"	76	6	7	2500
	80	6	7	2700
4"	90	6	6	3000
	102	6	6	3400
5"	105	6	6	3490
	114	6	6	4380
6"	127	6	6	4700
	152	6	6	6350