





LIFTING WINCHES

Type Grooved	Displacement (cm ³ /rev)	1. Wrap (daN)	4. Wrap (daN)	Pressure (Bar)	Lifting Speed (m/min)	Flow (lt/min)	Rope Dia. (mm)	Rope Length (m)
CP 130	127	1300	1000	165	59	60	10	62
CP 160	200	1600	1220	145	36	60	10	62
CP 200	250	2000	1530	165	33	60	10	62



LIFTING WINCHES

Type Straight	Dinamic Oil Equivalent	Displacement (cm ³ /rev)	1. Wrap (daN)	4. Wrap (daN)	Pressure (Bar)	Lifting Speed (m/min)	Flow (lt/min)	Rope Dia. (mm)	Rope Length (m)
CP 2000	P15	160	2000	1560	200	43	50	10	78
CP 2500	S 19/L	200	2500	1950	210	51	60	12	94
CP 3500	S 27/L	160	3500	2730	190	63	120	12	133
CP 4500	S35	200	4470	3500	210	38	80	14	105
TME 2	S45	200	5800	4510	225	43	120	15	105



GROOVED LIFTING WINCHES

Type Straight	Dinamic Oil Equivalent	Displacement (cm ³ /rev)	1. Wrap (daN)	4. Wrap (daN)	Pressure (Bar)	Lifting Speed (m/min)	Flow (lt/min)	Rope Dia. (mm)	Rope Length (m)
CP 2500F	S 19/L	200	2500	1940	210	51	60	12	94
CP 4500F	S35	200	4470	3500	210	38	80	14	105
TME 2-F-16	S45	200	5800	4480	220	42	120	16	96